

Outdoor 1080P/ 960P/ 720P IR 2M/1.3M/1M HD CVI Waterproof Camera Varifocal  
Lens with bracket



**Main Features:**

- >1/3" 1M,1.3M,2Megapixel CMOS
- >25/30/50/60fps@720P,960P,1080P
- >High speed, long distance real-time transmission
- >HD and standard definition switch.
- >OSD Menu, control over coaxial cable
- >Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- >2.8-12mm Varifocal lens (4-9mm, 3.5-8mm optional)
- >Max. IR LEDs length 50m, Smart 36Pcs IR leds
- >IP66, DC12V

**Technical Parameter:**

Model Number	FLA-QJ100WNX-HC	FLA-QJ130WNX-HC	FLA-QJ200WNX-HC
Image Sensor	1/2.9" 1Megapixel CMOS	1/3" 1.3Megapixel CMOS	1/3" 2Megapixel CMOS
Effective Pixels	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
Electronic Shutter	1/50s~1/100,000s	PAL: 4/25s~1/45,000s; NTSC: 4/30~1/54,000s	1/3s~1/100,000s
Video Frame Rate	25fps@720P, 30fps@720P	1280×720@25 fps ; 1280×720@30 fps; 1280×720@50 fps ; 1280×720@60 fps	1920'1080@25fps; 1920'1080@30fps; 1280'720@25 fps; 1280'720@30 fps; 1280'720@50 fps; 1280'720@60 fps
Synchronization	Internal		
Min. Illumination	0.01Lux@F1.2(0Lux IR LED on)		
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)		

Max. IR LEDs Length	50m, Smart 36pcs IR leds
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	3D/2D
OSD Menu	Support
Focal length	2.8-12MM (3.5-8MM,4-9MM optional)
Power Supply	DC12V±10%
Power Consumption	Max 6W
Working Environment	-30°C~+60°C Humidity is less than 95%(no condensation)
Transmission Distance	Over 500m via 75-5 coaxial cable
Weatherproof Protection	IP66
Packed Dimensions(W×D×H )	250x130x150mm ( Bracket included)
Weight(kg)	1.5KG